

MEGA OPACO

HIGHTLY CROSSLINKED METALLIZED MAT FLOOR POLISH



GENERAL DESCRIPTION

Formulation based on opaque polymers and waxes. It forms a film resistant to traffic marks and easy to clean and maintain.

It is suitable for the protection of PVC flooring, linoleum, terrazzo, etc. in high traffic areas, in hospitals and nursing homes. It can also be used for the protection of antistatic floors whom it does not change the electrical conductivity.

MEGA OPACO is also used for the natural-look finish of terracotta and stone floors.

DIRECTIONS FOR USE

Wash the floor with a wax stripper from the KEMIKA line and rinse. Apply two coats for greater protection. The second coat should be applied after the first has completely dried. For maintenance use TOC or GRIT. For dry maintenance use SPRAY NC and a rotary machine with red pad.

For the removal, use the specific wax stripper ECSTRA, or use DEKA P NEUTRO for linoleum floors.

TECHNICAL DATA

Appearance	white emulsion
pH	8.3 ± 0.2
Density	1.034 g/ml
Dry contents	21%
Active contents	27%
Coefficient of friction (ASTM 2047-75)	0.54

WARNINGS

Harmful to aquatic life with long lasting effects.

Contains: Methylchloroisothiazolinone, Methylisothiazolinone, 2-OCTYL-2H-ISOTHIAZOL-3-ONE, Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), Zinc ammonia carbonate complex. May produce an allergic reaction.

Keep from freezing and from heat: store at temperature between 10°-30° C. If correctly stored it does not change its property.

Product not classified dangerous.



KEMIKA Spa - Sede operativa e stabilimento
Via G. Di Vittorio 55 - 15076 Ovada (AL) ITALIA
Tel: ++39 (0) 143 80494 – Fax: ++39 (0) 143 823068
info@kemikaspa.com - www.kemikagroup.com

