


METALSPRAY

SPRAY BUFFING AID FOR HIGH SPEED MAINTENANCE OF METALLIZED FLOOR POLISHES



GENERAL DESCRIPTION

METALSPRAY is a composition of wax and polymers emulsions especially formulated for the maintenance of floor polishes films by spray buffing method with high speed machines.

METALSPRAY removes traffic marks and restores the gloss of the surfaces while adding new floor polish to the film.

METALSPRAY is available also in aerosol version.

DIRECTION FOR USE

Spray a small amount of **METALSPRAY** on the floor and buff with a high speed machine like the Novadisc 850 or Novadisc 1500 rpm until dry, to remove traffic marks and to achieve the "wet look" gloss.

Use special pads for "high speed" like the cream pad or the natural fiber pad.

Floor surfaces should be treated with ULTRAS, MONOMANO, MEGA or RESACRYL 2000 for an outstanding gloss.

TECHNICAL DATA

Appearance	white emulsion
pH	8.6 ± 0.2
Density	1.007 g/ml
Active contents	11%

WARNINGS

Harmful to aquatic life with long lasting effects.

Contains: Methylchloroisothiazolinone, Methylisothiazolinone, 2-OCTYL-2H-ISOTHIAZOL-3-ONE, REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1), Zinc ammonia carbonate complex. May produce an allergic reaction.

Keep from freezing.

The product is not classified as dangerous