

# RESIL

## DRY BRIGHT FLOOR POLISH FOR HYDROPHOBIC FLOORS



### GENERAL DESCRIPTION

**RESIL** is a water based floor polish zinc free, with special polymers for the protection of PVC floors that show adhesion problems to the normal floor polishes.

That kind of PVC floors have a polyurethane coating on the surface or are made with PVC / Paraffine blends.

Both treatment make the floor with hydrophobic (water repellent) properties.

**RESIL** shows also very good water and detergent resistance.

It is the product of choice for floors that demand frequent washings.

### DIRECTION FOR USE

For new floors, remove the original protective layer with DEKA P or DEKA P INODORE, rinse well and wait a few hours before applying **RESIL**. Apply **RESIL** with a wax applaier, wait until it is completely dry before applying the second coat.

Film maintenance: dust mopping or with antistatic products or with a damp microfibre flat mops. Wash with a neutral detergent like TOC. For dry maintenance use a medium or high speed single disc machine with METALSPRAY or SPRAY NC. For stripping use DEKA P (10-20%) and brown pad. Use DEKA P NEUTRO pH 7 for linoleum floors.

### TECHNICAL DATA

Appearance	White emulsion
pH	7.7 ± 0.2
Density	1.019 g/ml
Dry content	20.7%
Active content	26 ± 0.5 %
Coefficient of friction (ASTM D 2047-75)	0.51

### WARNINGS

Keep from freezing.

The product is not classified as dangerous



KEMIKA Spa - Sede operativa e stabilimento  
Via G. Di Vittorio 55 - 15076 Ovada (AL) ITALIA  
Tel: ++39 (0) 143 80494 – Fax. ++39 (0) 143 823068  
info@kemikaspa.com - www.kemikaspa.com

